


Mortise cylinders for Schlage L and HL Series locks

Security	Key mechanism	Pins	Patent protected keyway families	Functions	Full-face cylinders for L and N escutcheons L Series	Concealed body cylinder for L escutcheon L Series	Cylinders for sectional (rose) trim L and HL
Basic security Open keyways	Standard pin and tumbler	6	–[1]	All except below	30-021	30-004	30-001
				L9060 outside	26-021[2]	26-023	20-001[2]
	Check pin	6	S (Everest 29)	LM9280, LM/LMV9380 storeroom	30-019	--	30-000[5]
				L9485, L9486[4] faculty restroom/hotel	30-022[3]	30-005[3]	30-002[3]
Enhanced security Restricted use	Check pin	6	T (Everest 29)	All except below	30-021	30-004	30-001
				L9060 outside	26-021[2]	26-023	20-001[2]
				LM9280, LM/LMV9380 storeroom	30-019	–	30-000[5]
				L9485, L9486[4] faculty restroom/hotel	30-022[3]	30-005[3]	30-002[3]
	SL	7	R (Everest 29)	All except below	91-063	–	91-062
				L9060 outside	91-059	–	91-051
				LM9280, LM/LMV9380 storeroom	91-130 (1 1/4")	–	91-129 (1 1/8")
Upgraded security Primus level restricted use, geographic exclusivity, and independent sidebar	Legacy Primus	6	S, T (Everest 29)	All except below	20-793	20-789	20-787
				L9060 outside	20-701[2]	24-767	20-700[2]
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
	Primus RP	6	Obverse[1] (Classic)	All except below	20-793-RP	20-789-RP	20-787-RP
				L9060 outside	20-701-RP[2]	24-767-RP	20-700-RP[2]
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
	Primus XP	6	S, T (Everest 29)	All except below	20-793-XP	20-789-XP	20-787-XP
				L9060 outside	20-701-XP[2]	24-767-XP	20-700-XP[2]
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
	Primus XP SL	7	R (Everest 29)	All except below	91-760-XP	–	91-757-XP
				L9060 outside	91-754-XP	–	91-751-XP
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
High security All Primus benefits plus added UL 437 physical security	Legacy Primus	6	S, T (Everest 29)	All except below	20-593	20-589	20-587
				L9060 outside	20-501[2]	24-567	20-500[2]
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
	Primus RP	6	Obverse[1] (Classic)	All except below	20-593-RP	20-589-RP	20-587-RP
				L9060 outside	20-501-RP[2]	24-567-RP	20-500-RP[2]
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
	Primus XP	6	S, T (Everest 29)	All except below	20-593-XP	20-589-XP	20-587-XP
				L9060 outside	20-501-XP[2]	24-567-XP	20-500-XP[2]
				LM9280, LM/LMV9380, L9485, L9486	–	–	–
	Primus XP SL	7	R (Everest 29)	All except below	–	–	91-557-XP
				L9060 outside	91-564-XP	–	91-751-XP
				LM9280, LM/LMV9380, L9485, L9486	–	–	–



L and N Escutcheons


Cylinder only


L escutcheon


Concealed body cylinder


Sectional trim


HL Series


Compression ring and spring

1. Out-of-patent keyways like Classic Obverse are available. Obverse, however, can gain patent protection in a Primus RP or XP cylinder. RP is recommended because patent coverage carries to 2029 versus 2024 for Primus XP.
2. For L9060 outside applications that may require a longer cam - use L583-941 (1 1/8, 1 3/8, 1 5/8) and L583-942 (1 1/4, 1 1/2, 1 3/4).
3. Specify handing for faculty restroom/hotel cylinders.
4. L9486 available in Sectional (Rose)trim only.
5. Includes the L/LV9081 Accessible Storeroom function.

Note: 1 1/8" length standard. Optional lengths available in 1/8" (4mm) increments up to 1 3/4" (44mm).