Mortise cylinders

Mortise, rim and cam lock cylinders

Mortise, rim and cam lock for standard cylinders



Note: Specify finish - 605, 606, 613, 626, 629, 630

Mortise cylinder
900 Series cylinders are furnished with 5622-STD and 250 Series with 5622-STD unless otherwise specified.

See table for product numbers.

See pages 24-25 for optional cams and 26-27 for collars.



Note: Specify finish - 605, 606, 613, 626, 629, 630

Thumbturn cylinder
Furnished with 5622-STD except 970 Series furnished with 5622-STD unless otherwise specified.

See table for product numbers.

See pages 24-25 for optional cams and 26-27 for collars.



Note: Specify finish - 605, 606, 613, 625, 626

Dummy cylinder
Used to plug hole in door where lock remains but cylinder operation is no longer needed.

984D 1"
985D 1 1/8"



Note: Specify finish - 605, 606, 613, 626, 629, 630

Rim cylinder
Horizontal tailpiece standard. May be changed to vertical orientation in the field. Furnished with collar, back plate and 12-24 break off screws.

951 Specify 5, 6 or 7-pin

Specify cylinder number, keyway and finish when ordering.

Keyed mortise cylinders

Catalog number	Length	Pins	Application
985	1 1/8"	5 or 6	Generic
986	1 1/4"	5 or 6	Generic
987	1 3/8"	6 or 7	Generic
988	1 1/2"	6 or 7	Generic
990	1 3/4"	6 or 7	Generic
992	2"	6 or 7	Generic
250	1 1/8"	6	MA451 hotel function
251	1 1/4"	6	MA451 hotel function
252	1 3/8"	6	MA451 hotel function
253	1 3/8"	7	MA451 hotel function

Thumbturn mortise cylinders

Catalog number	Length	Pins	Application
985T	1 1/8"	—	Generic
986T	1 1/4"	—	Generic
973	1 1/8"	—	M911 Classroom thumbturn, RH (CCW)
974	1 1/8"	—	M911 Classroom thumbturn, LH (CW)



Note: Specify finish - 605, 606, 613, 626, 629, 630

Cam lock - heavy cam
Includes stop washers for rigid and lazy cam operation. Field reversible for RH or LH doors by positioning of stop screw on back of housing. Requires 1 3/16" cylinder hole and fits doors up to 1 1/8" thick.

945 Specify 5 or 6-pin



Note: Specify finish - 606, 626

Mailbox cylinder
U.S. Postal regulations prohibit master keying of mailbox locks. Mailboxes must be ordered specifically for Falcon cylinders from the mailbox manufacturer.

954 Specify 5, 6 or 7-pin