


MODEL PB2	A	B	C	D	DEPTH
	4.5	2.75	.625	1.375	3

NOTE: FASTENERS NOT SHOWN ALL DIMENSIONS IN INCHES.



PUSH BUTTON - MODEL PB2

Features

- SPDT 10 amp contacts (DPDT available, see How to Order section)
- Large 2" diagonal flush button
- Momentary operation
- 12/24 VDC LED button illumintaion and a red LED (illuminated version only)
- Stainless steel single gang plate (back box included on illuminated versions)

Operating Temperatures

0 to 43C [32 to 110F]

Options

- **H –** Handicap
- **E –** Economy non-illuminated
- **2 -** DPDT

© 2015, Hanchett Entry Systems, Inc., an ASSA ABLOY Group company.

PUSH BUTTON - MODEL PB2 (cont'd)

How to Order

Part #	Description
PB2	Push Button 2" Square Mom. SPDT Single Gang Illuminated
PB2H	Push Button 2" Square Mom. SPDT Handicap Illuminated
PB2E	Push Button 2" Square Mom. SPDT Single Gang
PB2EH	Push Button 2" Square Mom. SPDT Handicap
PB2-2	Push Button 2" Square Mom. DPDT Single Gang Illuminated

Architectural Specifications

A. The Push Button shall be produced by an ISO 9001 certified manufacturer.

B. The Push Button shall be a 2" by 2" industrial grade button with protective cowling.

C. The Button shall be labeled 'EXIT" and shall be green back lit using an incandescent bulb. A separate red LED shall be provided as an additional indicator.

D. The LED's shall operate on 12 or 24 VDC (field selectable).

E. The switch shall be SPDT and rated at 10 Amps at 12 or 24 VDC.

F. The push button shall be mounted on a Stainless Steel - 630/US32D single gang faceplate.

G. The switch shall be available in momentary action in both illuminated and non-illuminated versions.