BEST

dormakaba Group



HD8000
HD7000
SL6000

Surface Applied Door Closers



SL6000 SERIES SURFACE CLOSERS



The SL6000 Series surface closer offer modern styling and versatility while providing safe and reliable
door control.

Featuring backcheck and adjustable spring sizes, SL6000 is the ideal solution in a wide variety of applications, including barrier-free. This Grade 1 hydraulic surface door closer is both flexible and easy to install. The SL6000 offers a compact design and is available in a variety of sprayed finishes to complement any opening's decor.

SL6000—Features

- Available with adjustable spring sizes 1–4 and with adjustable spring sizes 3–6.
- Meets 5 lb interior barrier-free applications. (SL6014 only)
- Non-handed for regular, top jamb and parallel arm applications.
- Quick and easy to install.
- Compact design.
- Two noncritical adjusting valves (sweep and latch) with thermostatic properties work to provide consistent closing speeds under a wide variety of temperatures.
- Adjustable backcheck standard. Provides cushioning when the door is abusively opened.
- Available with optional delayed action to delay door closing from maximum opening. Delay time is adjustable.
- SNDTPK - Standard fasteners include separate self-drilling and self-tapping and sex nuts for 1-3/4" thick doors and machine screws.
- SL640C mounting bracket can be used when installing into a 9-1/16" template hole pattern.
- Optional slim plastic cover

SL6000—Certification

- ANSI/BHMA A156.4 Grade 1 certified
- UL and CUL listed
- Meets UL10C for positive pressure

dormakaba USA quality and environmental management systems in Reamstown, PA and Indianapolis, IN are certified to ISO 9001:2015 and ISO 14001:2015.