www.sdcsecurity.com service@sdcsecurity.com
[t] 800.413.8783 805.494.0622 [f] 805.494.8861
801 Avenida Acaso, Camarillo CA 93012 • PO Box 3670, Camarillo CA 93011-3670

Transformers & Plug-In DC Power Supplies



TR12

Plug-in DC Power supply with 2 secondary outputs.

- Primary: 120VAC, Grounded
- 1 Fused, Unregulated Lock Output: 12VDC @ 780 mA
- 1 Regulated Access Control Output: 12VDC @ 150 mA
- Screw Terminals



TR24

Plug-In DC Supply

- Primary: 120VAC, grounded
- Secondary: Fused, unregulated 24VDC @ 1Amp
- 6 Ft. Cord



TP1220

Plug-In Transformer

- Primary: 120VAC
- Secondary: fused, 12VAC @ 1.65Amps (screw terminals)
- UL Listed, Class 2



TP2440

Plug-In Transformer

- Primary: 120VAC
- Secondary: fused, 24VAC @ 1.65Amps (screw terminals)
- UL Listed, Class 2



TJ2440

J-Box or Base Mounted Transformer

- Primary: 120VAC (wire leads)
- Secondary: 24VAC @ 1.65Amps (screw terminals)
- UL Listed, Class 2



TB2450

Base Mounted Transformer

- Primary: 120VAC/240VAC (screw terminals)
- Secondary: 24VAC @ 2Amps (screw terminals)
- Field replaceable fuse
- UL Listed



TB2475

Base Mounted Transformer

- Primary: 120VAC/240VAC (screw terminals)
- Secondary: 24VAC @ 4Amps (screw terminals)
- Field replaceable fuse
- UL Listed



BR64XL

Full Wave Bridge Rectifier

- Input: 12 or 24VAC
- Output: 12 or 24VDC
- 4 Amps Maximum Load

© 2012 Security Door Controls LIT-Transformers 09/12
M:\Marketing Files\In-House Pubs\Datasheets\Power Supplies\Transformers.indd