CAMDEN DOOR CONTROLS

COMPARISON CHART

SURE-WAVE™ BY CAMDEN



CM-324 SURE-WAVE™ BY CAMDEN HANDS-FREE SWITCH

DESCRIPTION	CAMDEN CM-324	SECO LARM 927	MS SEDCO 216	BEA MS-08	LARCO U-WAV	BIRCHER PROXY SWITCH	THE CAMDEN ADVANTAGE
Technology Used	**Active Infrared**	Active Infrared	Active Infrared	Doppler Radar	Doppler Radar	Active Infrared	Infra-Red is more stable and less prone to RF interference.
Range (with hand)	**1" - 26"**	0– 4"	6 – 22"	2 – 20"	4 – 20"	2 – 24"	Longest range.
Adjustable Hold Time	**1-5 seconds**	Non-Adjustable	1-5 seconds	0.5-10 seconds	0.5-10 seconds	Non-Adjustable	Great for de-activating mag-locks & strikes.
Operating Modes	**Sense / Toggle**	Sense	Sense / Toggle	Sense / Toggle	Sense / Toggle	Sense	The most versatile. Toggle works like a light switch.
Fail-Safe Mode?	**Yes**	No	Yes	No	No	No	Extra safety during a power failure.
Presence Detection w/Non-Moving Object	**Yes**	Yes	No	No	No	Yes	Inherently more safe. Relay will not drop out if hand is stationary.
Ability to Mount in the Jamb?	**Yes**	No	Yes	No	No	No	The most varied sizes and designs available on the market = a fit for every application and mounting challenge.
Faceplate Sizes Available	**Jamb Single Gang Double Gang**	N/A Single Gang N/A	Jamb Single Gang Double Gang	N/A Single Gang Double Gang	N/A Single Gang N/A	N/A Single Gang N/A	
Faceplate Designs: • Plain • Waving Hand • Waving Hand + Wave to Open	**Yes Yes Yes**	No No No	Yes No Yes	Yes No Yes	No Yes No	Yes No No	
LED Shut-off	**Yes**	No	No	No	No	No	Exclusive Camden feature.
Relay Output	**Form C**	Form C	Form C	Form C	Form C	Form C	The industry standard.
Relay Contact Rating	**5 Amps.**	3 Amps.	3 Amps.	1 Amp.	1 Amp.	1 Amp.	Rugged and durable.
Gasket Included for Outdoor Mounting	**Yes**	No	No	Yes	No	Yes	Suitable for outdoors, clean rooms, mfg. plants.
Voltage	**12-24V AC/DC**	12V DC	12-24V AC/DC	12-24V AC/DC	12-24V AC/DC	12-24V AC/DC	Suitable for all applications.

Note: Specifications are subject to change without notice. (April 24, 2012)