
CRXA-Heavy Duty Ligature Resistant Cylindrical





Specification

- ANSI Grade 1 heavy duty cylindrical with 5-point ligature resistant arch trim
- Backset 2-3/4" standard, 5" optional
- Door thickness: 1-3/4", other upon request
- Stainless steel arch trim, 2-5/8" projection
- Stainless steel plate, 9-5/8" x 2-13/16"
- Stainless steel deadlocking latch bolt, ½" throw
- Stainless steel ASA strike standard
- Tamper resistant mounting screws
- Handed, specify handing
- Cylinder:
  Schlage® "C" keyway, brass 6 pin cylinder standard
  Best® Small Format I.C. available, 6 or 7 Pin, with or without core.
  Schlage® Large Format I.C. less core available
  Corbin® Large Format I.C. less core available
  High security cylinder available, TownSteel "L" keyway, 6 pin
- Keying: KD standard, KA, MK, GMK, GGMK and construction keying available
- Available functions: F-75, 76, 84, 86, Single Dummy (F-41), Pair Dummy(F-72)
- Door Prep: 161 plus 2-1/8" cylinder hole and ½" bottom post hole
- 10-year manufacturer's limited warranty

Code Compliance

- ANSI/BHMA A156.2-2011 Grade 1 certified
- UL 10C Listed 3-Hour Fire Rating
- Meets guidelines of The Americans with Disabilities Act
- Meets requirements of The Buy American Act
- OMH of New York State Approved

Available Function

ANSI CODE	DESCRIPTION
F-75	Passage
F-76	Privacy
F-84	Classroom
F-86	Storeroom
F-41	Single Dummy
F-72	Pair Dummy

Important Note:

It is TownSteel's position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer's cylinder is to be used in place of the TownSteel original manufacturer's cylinder, that a sample of that product be provided to TownSteel in advance for testing.

TownSteel® Architectural Hardware MFG
17901 Railroad Street City of Industry, CA 91748 Toll Free: 877-858-0888
Tel: 626-965-8917 Fax: 626-965-8919 www.townsteel.com