MRX-E-L-Heavy Duty Ligature Resistant Mortise



MRXL-26 (INSIDE)

Specification

- ANSI Grade 1 heavy duty mortise lock with ligature resistant lever trim
- Available in sectional and escutcheon
- Backset 2-3/4”
- Door thickness: 1-3/4” standard, other upon request
- Stainless steel lever trim
- Stainless steel latch bolt, split, anti-friction, ¾” throw
- Stainless steel dead bolt, with anti-saw pins, 1” projection
- Stainless steel ADA thumb turn standard
- Stainless steel ANSI strike
- Tamper resistant stainless steel mounting screws
- Handed, field reversible
- Schlage “C” keyway, brass 6 pin cylinder standard
- SFIC with or less core available, 6 or 7 pin core
- Schalge® LFIC less core available
- Corbin® LFIC less core available
- High security cylinder available, TownSteel “L” keyway, 6 pin
- High security SFIC core available, TownSteel “L” keyway, 7 pin
- KD, KA, MK, GMK, GGMK and construction keying available
- Available functions: F-01, 02, 04, 05, 07,13, 22, 26, visit townsteel.com for more available functions
- Available finish: US32D
- 10-year Manufacturer’s Limited Warranty

Code Compliance

- ANSI/BHMA Certified A156.13-2005 Grade 1 Certified
- UL 10C Listed 3-Hour Fire Rating
- Meets requirements of The Buy American Act
- Meets requirement of The Americans with Disabilities Act

Important Note:

It is TownSteel’s position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer’s cylinder is to be used in place of the TowsnSteel original manufacturer’s cylinder, that a sample of that product be provided to TownSteel in advance for testing.

TownSteel® Architectural Hardware MFG

17901 Railroad Street City of Industry, CA 91748 Toll Free: 877-858-0888
Tel: 626-965-8917 Fax: 626-965-8919 www.townsteel.com