TRXL-Heavy Duty Ligature Resistant Cylindrical



TRXL-84 (OUSIDE)

Specification

- ANSI Grade 1 heavy duty cylindrical with ligature resistant lever trim
- Backset 2-3/4" standard, 5" optional
- Door thickness: 1-3/4"-2"
- Stainless steel lever trim
- Stainless steel deadlocking latch bolt, ½" throw
- Stainless steel ASA strike standard
- Tamper resistant mounting screws
- Non-handed
- Schlage "C" keyway, brass 6 pin cylinder standard
- SFIC with or less core available, 6 or 7 pin core
- High security cylinder available, TownSteel "L" keyway, 6 pin
- High security SFIC core available, TownSteel "L" keyway, 7 pin
- KD, KA, MK, GMK, GGMK and construction keying available
- Available functions: F-75, 76, 81, 84, 86, 87
- Available finish: US32D
- 10-year Manufacturer's Limited Warranty

Code Compliance

- ANSI/BHMA Certified A156.2-2011 Grade 1 Certified
- UL 10C Listed 3-Hour Fire Rating
- Meets requirements of The Buy American Act
- Meets requirement of The Americans with Disabilities Act

Important Note:

It is TownSteel's position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer's cylinder is to be used in place of the TowsnSteel original manufacturer's cylinder, that a sample of that product be provided to TownSteel in advance for testing.

TownSteel®
Architectural Hardware MFG

17901 Railroad Street City of Industry, CA 91748 Toll Free: 877-858-0888
Tel: 626-965-8917 Fax: 626-965-8919 www.townsteel.com