DRX TEMPLATE

DOOR PREPARATION CHART

LOCK FUNCTION	OUTSIDE	INSIDE
09	Cylinder Hole	Cylinder Hole
16	Thumb Turn Hole	
07		Thumb Turn Hole
18		

HEAVY DUTY DEADBOLT

4-1/4" (108mm)

2-3/4" (70mm) **BACKSET**

1-1/8" (28.6mm)

4-5/8" (117.5mm)

3-63/64" (101.1mm)

2-7/8" (73mm)

1" (25.4mm)

1-1/4" (32mm)

O/S

23/32" (18.3mm)

15/32" (12mm)

1/2" (12.7mm)

Y/S

OUTSIDE-ONLY

INSIDE-ONLY

Of LOCK

5/64" (2mm)

Of Strike

7/32"(5.5mm)

2 x 12-24 TAP FOR METAL DOORS

Of Lock And Door Thickness

HIGH BEVEL

LOW BEVEL

FLAT NO BEVEL

Match To Door

1" 25.4mm

If This Measures 1" or 25.4mm Scale Is Correct

LOCATOR POINT

MATCH WITH VERTICAL LINE DRAWN ON DOOR

RESPONSIBILITY

Door and Frame Manufacturers are responsible for providing adequate construction or reinforcements for proper installation of hardware shown. All architectural builders hardware must be installed on properly reinforced doors and frames, regardless of the type, material or method of construction.

FOR OPPOSITE HAND, PLEASE SEE REVERSE SIDE

09/17/10

RECESS TO FIT STRIKE PLATE

2 x 12-24 TAP FOR METAL DOORS

1-1/8" 28.6mm

3/4" 19.05mm

2-1/2" (63.5mm)

1-7/8" (47.63mm)

1-1/8" (28.58mm)

1-1/8" 28.58mm DEEP

3-1/2" 88.9mm

Of Door

DOOR FRAME VIEW

STRIKE TEMPLATE