



In or Out...we make it Easy!®



8360

Mortise MiniMag®
For Sliding Doors

1-1/16"D x 1-1/2"W x 9"L
(26.9mm x 38.1mm x 228.6mm)



8365

Mortise MicroMag®
For Sliding Doors

13/16"D x 1-11/32"W x 7-15/16"L
(20.6mm x 34.1mm x 201.6mm)

Features & Benefits

- Brushed Anodized Aluminum finish
- Low energy consumption
- Field-selectable voltage 12/24VDC
- MOV surge protection
- Hardened steel armature nut
- Built-in Remote Lock Status (RLS) (8360 only)
- No residual magnetism
- Low-profile design

Mortise MiniMag®

Our low-profile 8360 mortise MiniMag® is specifically designed to provide a secure hold (up to 750 lbs. holding force) on sliding doors.

Mortise MicroMag®

The compact 8365 mortise MicroMag®, with up to 300 lbs. holding force, is designed as an even lower-profile magnet for sliding doors, cabinets and jewelry cases and small enclosures.

Highlights

- Low-profile & compact designs
- Up to 750 lbs. holding force (8360)
- Up to 300 lbs. holding force (8365)
- Dual voltage
- Lifetime Warranty

Applications

PERIMETER AND INTERIOR SLIDING DOORS
SMALL ENCLOSURES

- Cash drawers
- Vending machines
- Filing cabinets
- Access cover hatches
- Industrial
- Commercial
- Residential
- Health Care
- Retail



In or Out...we make it Easy![®]


NOTE: Specifications are subject to change without notice.

Specifications	8360	8365
Housing Dimensions	1-1/16" D x 1-1/2" W x 9" L (26.9 x 38.1 x 228.6mm) (including 3/4" mounting tabs)	13/16" D x 1-11/32" W x 7-15/16" L (20.6 x 34.1 x 201.6mm) (including 11/16" mounting tabs)
Armature Plate Dimensions	1/2" D x 1-1/2" W x 7-1/4" L (12.7 x 38.1 x 184.2mm)	5/16" D x 1-1/4" W x 5-1/8" L (7.9 x 31.8 x 130.2mm)
Voltage	Field selectable 12/24 VDC Tolerance ±10%	Field selectable 12/24 VDC Tolerance ±10%
Power/Current Requirements	Max 0.50A at 12 VDC Max 0.25A at 24 VDC	Max 0.40A at 12 VDC Max 0.20A at 24 VDC
Holding Force	One-point locking (up to 750 pounds)	One-point locking (up to 300 pounds)
Output Contacts	0.20A @ 12 VDC and 0.12A @ 24 VDC Dry Output Form C	N/A
Wiring Requirements	2 wires – power input 2 wires – relay output	2 wires – power input

NOTE: RCI recommends frame reinforcement and our filtered, regulated DC voltage 10 Series power supplies.

Function Descriptions

Remote Lock Status (RLS) Output	A Form C reed switch output offers lock status remote indication capability. (8360 Only)
---------------------------------	--



8360/8365 Typical Installation

RCI also offers a complete line of Electromagnetic Locks, Electric Strikes, Electric Locks, Power Supplies, Switches, Keypads & Readers, Exit Devices, Systems & Door Hardware.