Keypads & Readers

9325i & 9325e

9 Series Digital Access Control

RUTHERFORD CONTROLS

In or Out... we make it Easy!®





9325i Backlit Interior Keypad

9325e Backlit Weatherproof Exterior Keypad

Dimensions
2-3/4"W x 4-1/2" H x 1-5/32" D
(70.mm x 115.0mm x 29.0 mm)

Features & Benefits

- Accommodates up to 120 users
- Safe storage of data (all data is stored in the event of a power failure)
- Secure access codes (4-8 digits)
- Backlighting (can be disabled)
- Silent Mode (audible annunciation of keypresses can be disabled)
- Programmable lockout
- Variable output time delay (1-60 sec.)
- Surface mount design
- Interior/Exterior (separate models)
- 12VDC

Stand-Alone Keypads

Elegant, yet durable, the 9325i and 9325e are cost efficient keypads that blend in with any decor. Ideal for interior or exterior applications (depending on model), this keypad can accommodate up to 120 users.

Data safe – even in the event of a power failure, your 6-digit master code and all other data is still stored.

For efficient use in poorly lit areas, the keypad features backlighting (which can be disabled). Silent mode can also be enabled if audible annunciation of keypresses is not desired.

Highlights

- Accommodates 120 Users
- Microprocessor and EEPROM Technology
- Keypad Programmable
- 2-Year Limited Warranty

Applications

- Commercial
- Office Buildings
- Warehouses
- Industrial
- Residential
- Healthcare

Accessories

T1003. . . . . Plug-In/UL transformer
10-175UL. . . . . Power supply with fire alarm interface
1012NR . . . . . Power Supply, no relay
1012FPD-1A . . Power Supply with Fire Panel Disconnect
1012FPD-2A . . Power Supply with Fire Panel Disconnect
10-5-PDD-FT . . Power Supply comes with Power Distribution Device-Fire Trigger
10-5 . . . . . Power Supply only
9310RB . . . . . Relay Board

©2011 RUTHERFORD CONTROLS INT'L CORP. WWW.RUTHERFORDCONTROLS.COM
USA: 2517 SQUADRON COURT, SUITE 104, VIRGINIA BEACH, VA 23453 • CANADA: 210 SHEARSON CRESCENT, CAMBRIDGE, ON N1T 1J6
PHONE • 1.800.265.6630 • 519.621.7651 • FAX: 1.800.482.9795 • 519.621.7939 • E-MAIL: SALES@RUTHERFORDCONTROLS.COM

Specifications

9325i & 9325e

RUTHERFORD CONTROLS

In or Out... we make it Easy!®

Description of Features	
Memory	Non-volatile EEPROM memory means your codes and instructions will be there whether you remove power for five minutes or five years.
Main Relay	Rated at 5 amps, this Form A relay is tough enough to handle virtually any low-voltage equipment or electronic locking device.
Remote Triggering Input	Each keypad provides a normally open input loop for remote triggering. Simple programming allows for a momentary closure upon this loop to trigger the output. This feature is especially useful as an exit request and can be disabled in software.
Programming	All programming is accomplished entirely from the front of the keypad. LED and/or sounder guidance makes programming a snap and changing codes a matter of seconds for an authorized user.
Expanded Memory	Comes with enough memory to support up to 120 users.
Exit Toggle	Activating this feature will cause the exit button to delay the doors' locked state until the code has been re-entered. By default the exit button will unlock the door for the programmed door unlock time.
9325i Output Mode	Keypad can be jumper configured as SPST relay output or 12VDC powered output rated at 1A max.

Specifications	
Keypad Dimensions	2-3/4"W x 4-1/2" H x 1-5/32" D (70.0 x 115.0 x 29.0 mm)
Number of Users	Up to 120
Voltage Input	12 VDC
Relay Rating	5A @ 30VDC
Warranty	2 years

RCI also offers a complete line of Electromagnetic Locks, Electric Strikes, Power Supplies, Switches, Keypads & Readers, Exit Devices, Systems & Door Hardware.

©2011 RUTHERFORD CONTROLS INT'L CORP. WWW.RUTHERFORDCONTROLS.COM
USA: 2517 SQUADRON COURT, SUITE 104, VIRGINIA BEACH, VA 23453 • CANADA: 210 SHEARSON CRESCENT, CAMBRIDGE, ON N1T 1J6
PHONE • 1.800.265.6630 • 519.621.7651 • FAX: 1.800.482.9795 • 519.621.7939 • E-MAIL: SALES@RUTHERFORDCONTROLS.COM