SPECIALTY LOCKS

EM-MAG1500

COMPACT ELECTROMECHANICAL LOCK

Energy
240mA[1]
Field-Selectable
12/24VDC

Strength
1,500lbf
Holding Force

Mode
Fail-Safe

Monitor
Lock & Door
Status Sensors

Warranty
3 Year Limited
Warranty

[1]At 12VDC, 120mA at 24VDC



For outswing doors & small enclosures.

© 2016 Rutherford Controls Int'l I A DORMA Group Company
www.rutherfordcontrols.com • E-mail: sales@rutherfordcontrols.com
Phone: 1.800.265.6630 • Fax: 1.800.482.9795

Features

- Slim design; significantly smaller than standard electromagnetic locks
- Bi-color light panel indicates lock status
- Releases under side load of up to 130lbs (60kg)
- Early warning alarm
- Includes anti-tamper security plate
- Anodized aluminum housing; zinc plated for anti-corrosion
- No residual magnetism
- Low energy consumption
- Factory tested to over 1-million cycles

Applications

- Buildings
- Hotels
- Lockers
- Cabinets

Specifications

Voltage	Current	Duty
12VDC	240mA	Continuous
24VDC	120mA	Continuous

Dimensions

6-7/32"W x 1-7/16"H x 1-3/8"D (158mm x 36mm x 35mm)
Armature Plate:
4-3/4"W x 1-3/16"H x 1/2"D (121mm x 30mm x 12.5mm)

ZLEM-MAG1500
R02/16CL