SPECIALTY LOCKS

MEM2400

COMPACT ELECTROMECHANICAL LOCK

Energy
350mA[1]
Field Selectable
12/24VDC

Strength
1500lbf
Holding Force

Mode
Fail-Safe

Monitor
Lock & Door
Status Sensors

Warranty
3 Year Limited
Warranty

[1]At 12VDC, 175mA at 24VDC



For inswing doors & small enclosures.

Features

- Patented electromagnetic lock with early warning detectors
- Bi-color LED light indicates lock status
- Compact surface-mount design
- Includes adjustable L & Z bracket
- Capable of releasing under door back pressure (pre-load) of up to 150lbs (70kg)
- Aluminum extrusion casing and anodized coated, high grade zinc plating on magnet and plate
- No residual magnetism
- Low energy consumption

Applications

- Buildings
- Hotels
- Lockers
- Cabinets

Specifications

Voltage	Current	Duty
12VDC	350mA[1]	Continuous
24VDC	175mA	Continuous

Dimensions

8-5/8"W x 1-7/16"H x 1-3/8"D (218mm x 36mm x 35mm)
Armature Plate:
7-1/8"W x 1-3/16"H x 1/2"D (181mm x 30mm x 12.5mm)

© 2016 Rutherford Controls Int'l I A DORMA Group Company
www.rutherfordcontrols.com • E-mail: sales@rutherfordcontrols.com
Phone: 1.800.265.6630 • Fax: 1.800.482.9795