

7000

Series

The pre-load solution for high traffic openings

Specifications

- UL 1034, burglary-resistant listed
- ANSI/BHMA A156.31, Grade 1 (791 and 792 options)
- ANSI/BHMA A156.31, Grade 2 (783S, 786S and 789S options)
- MEA New York City accepted
- Patent #5,484,180

Standard Features

- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs. (791 and 792 options)
- Dynamic strength 70 ft-lbs. (791 and 792 options)
- Static strength 1,000 lbs. (783S, 786S and 789S options)
- Dynamic strength 50 ft-lbs. (783S, 786S and 789S options)
- Endurance 500,000 cycles
- Field selectable fail secure/fail safe
- Accommodates pre-load (fail secure only)
- Horizontal adjustment
- Non-handed
- Internally mounted solenoid
- Strike body depth 1-11/16"
- Plug-in connector
- Trim enhancer (791 and 792 options)
- Pocket adapter (786S and 792S options)
- Three year limited warranty

Optional Features

- LBM - Latchbolt monitor

Electrical

- .45 Amps @ 12VDC continuous duty
- .25 Amps @ 24VDC continuous duty

Finishes (791 and 792 options only)

- 630 - Satin stainless steel
- 605 - Bright brass
- 606 - Satin brass
- 612 - Satin bronze
- 613C - Brown nylon powder coated finish
- 629 - Bright stainless steel
- BLK - Black

Finishes (783S, 786S and 789S options)

- 613C - Brown nylon powder coated finish
- 626 - Brushed chrome

Frame Application

- Metal
- Wood

