

CRL Jackson® 1200 Series Panic Exit Devices

- Designed for Use With 1-3/4" (44 mm) Narrow, Medium, and Wide Stile Aluminum, Wood or Hollow Metal Doors
- "Soft-Touch" Smooth Action Push-Pad
- Can Be Cut to Size
- Standard Hex Key Dogging

This CRL Jackson® Exit Device blends the reliability of the time-proven 10 Series Crossbar Device with the sleek, contemporary style of today's modern push-pad exit device. For additional product information, visit our web site at crlaurence.com/panic-devices.



'C' Strike



'S' Strike

MORE MODELS
crlaurence.com

36" (914 MM) DOOR CAT. NO.	48" (1219 MM) DOOR CAT. NO.	TYPE	HANDING	FINISH
31127537628	31127547628	84" Surface Vertical Rod	Non-Handed	Satin Aluminum
31127537313	31127547313	84" Surface Vertical Rod	Non-Handed	Dark Bronze
31127538628	31127548628	96" Surface Vertical Rod	Non-Handed	Satin Aluminum
31127538313	31127548313	96" Surface Vertical Rod	Non-Handed	Dark Bronze
311285L37628	311285L4628	Concealed Vertical Rod	LH Reverse Bevel	Satin Aluminum
311285L37313	311285L4313	Concealed Vertical Rod	LH Reverse Bevel	Dark Bronze
311285R37628	311285R4628	Concealed Vertical Rod	RH Reverse Bevel	Satin Aluminum
311285R37313	311285R4313	Concealed Vertical Rod	RH Reverse Bevel	Dark Bronze
311295C3628	311295C4628	Rim Device - 'C' Strike	Non-Handed	Satin Aluminum
311295C3313	311295C4313	Rim Device - 'C' Strike	Non-Handed	Dark Bronze
311295S3628	311295S42628	Rim Device - 'S' Strike	Non-Handed	Satin Aluminum
311295S3313	311295S42313	Rim Device - 'S' Strike	Non-Handed	Dark Bronze

Minimum order: 1 each. All Panic Exit Devices can be combined for quantity pricing.

Cylinder Dogging

Cylinder dogging is available when specified by adding "C" behind the model series number. The Exit Device is supplied with the required prep and special cam only that is required to be used with a 1-1/4" Mortise Cylinder that is not supplied with the device and must be purchased separately. See DC7205SCK Series on page CH206. **Example:** 312095'C'LC3628


UL is a registered trademark of UL LLC.



Model 1275



Model 1285



Model 1295

SPECIFICATIONS:

1275 Surface Vertical Rod Device

- Stocked in Both 36" and 48" (914 and 1219 mm) Widths
- Standard Door Heights 84" (2134 mm) and 96" (2438 mm) – Field Sizeable

1285 Concealed Vertical Rod Device

- Stocked in Both 36" and 48" (914 and 1219 mm) Widths
- Standard Height 84" (2134 mm) - Extension Available; See page CH082
- Requires Series 30821J Cylinder Mounting Pad When Using Mortise Cylinder for Keyed Outside Entry; See pages CH082 and CH206

1295 Rim Device

- Stocked in Both 36" and 48" (914 and 1219 mm) Widths
- Surface Mounted Roller Strike Standard
- Requires Rim Cylinder for Keyed Entry; See page CH206.

MATERIALS:

Base and Push-Pad: Extruded Aluminum
 Mechanical Components: Stainless and Hardened, Plated Steel
 Latch and Strikes: Sintered Steel
 Metal End Caps



Cylinder Dogging Models Available