



Catalog Number See Table
 UPC Number
 Description Pre- Insulated Crimp Connectors
 Wire Joint

Features
 · Polyimide Nylon 6/6 Insulation
 · Tin plated Copper Sleeve

General
 Conductor Range: See Table

Dimension Information
 See Table

Specifications
 Temperature Rating 105°C
 Voltage Rating 300
 Flammability Rating UL 94V-2
 Amp Rating To Conductor

Packaging
 Box Qty See Table

Certifications
 UL Yes
 cUL Yes
 RoHS Yes

Cat No.	Wire Range	Max	Min	A	B	C	D	E	Bag Qty	Master Qty	Per 100
Hanging Bag 25 Pack											
22100	22 - 18 Awg	2 #20 & 1 #18	2 #22	0.102	0.244	0.307	0.244	0.709	25	100	
22102	22 - 14 Awg	1 #18 & 1 #14	2 #22	0.118	0.311	0.374	0.283	0.776	25	100	
22104	22 - 10 Awg	3 #14	2 #22 & 2 #18	0.157	0.413	0.492	0.378	1.004	25	100	
22106	16 - 10 Awg	2 #16 & 1 #10	2 #16 & 1 #12	0.209	0.488	0.575	0.472	1.091	25	100	
Bagged 100 Pack											
22000	22 - 18 Awg	2 #20 & 1 #18	2 #22	0.102	0.244	0.307	0.244	0.709	100	1000	
22002	22 - 14 Awg	1 #18 & 1 #14	2 #22	0.118	0.311	0.374	0.283	0.776	100	1000	
22004	22 - 10 Awg	3 #14	2 #22 & 2 #18	0.157	0.413	0.492	0.378	1.004	100	1000	
22006	16 - 10 Awg	2 #16 & 1 #10	2 #16 & 1 #12	0.209	0.488	0.575	0.472	1.091	100	1000	
High Temperature 150°F Bagged 100 Pack											
22007	22 - 14 Awg	1 #18 & 1 #14	2 #22	0.118	0.311	0.374	0.283	0.776	25	100	
22008	22 - 10 Awg	3 #14	2 #22 & 2 #18	0.157	0.413	0.492	0.378	1.004	25	100	

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804