




Catalog Number 23192 - 23282
UPC Number
Description Grounding Wire Connector



Features

- Ribbed-Cap provides a more secure grip and faster fingertip starts even when hands become slippery
- Built-in swept-back designed wing enables users to tighten connectors easily without tools
 - Color coded Green for quick identification as grounding connector
- Specifically designed for making positive ground connections and bonding non-metallic sheathed cable
- Live action square spring draws wires deep into spring for safe, tight grip
- No pre-twisting of conductors is required – spring creates its own thread
- Reusable connector threads on or off splice for fast and easy circuit changes and additions
- Tough, UL 94V-2 Flame retardant shell will not crack or break, even when applied to maximum wire combinations under extreme pressure

General

Material: Heavy Duty Thermoplastic
 Spring Steel Wire Core

Dimension Information

See Engineering Dwg

Specifications

Flammability Rating: UL 94V-2
Temperature Rating: 212 ° F (105°C)
Voltage Rating: 600V 1000V Lighting Fixtures & Signage

Packaging

Bag Qty See Table

Certifications

UL UL 486C
cULus cULus
ROHS Yes

No.	Color	Wire Combinations	A	B	C	D	E	Bag Qty	Case Qty
23292	Green	No.14 Thru 10 Awg	0.327	0.476	0.795	0.370	1.134	25	5,000
23092	Green	No.14 Thru 10 Awg	0.327	0.476	0.795	0.370	1.134	100	10,000
23192	Green	No.14 Thru 10 Awg	0.327	0.476	0.795	0.370	1.134	500	5,000