



Catalog Number See Table
UPC Number
Description One Conductor Two Hole Aluminum Mechanical Lug

- Features**
- Manufactured from High Strength High Conductivity Aluminum Alloy
 - Electro-Tin Plated
 - CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
 - Two Mounting Holes - NEMA Spacing

General

Conductor Size: See Table
 Material: 6061-T6 Aluminum Alloy
 Finish: Electro-Tin Plating
 Screw Type: 300 Thru 1000 MCM

Dimension Information

See Table

Specifications

Temperature Rating 90° C
 Voltage Rating 600
 Flammability Rating N/A
 Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL 486B UL 41968 CU9AL Dual Rated
 CSA LR27194
 RoHS Yes

Cat No.	AWG	Fig.	Wire Range	Box Qty	L	W	H	Bolt	
ONE CONDUCTOR - TWO HOLE MOUNT									
90731	300	3	300MCM - 6SQL	6	4	0.93	1.12	0.56	
90732	350	3	350MCM - 6SQL	3	4	0.93	1.12	0.56	
90734	600	3	600MCM - 2SQL	3	4.36	1.19	1.59	0.56	
90735	750	3	750MCM - 300MCM	1	4.75	1.75	1.75	0.56	
90736	1000	3	1000MCM - 500MCM	1	4.75	1.75	1.75	0.56	