



Catalog Number See Table  
 UPC Number  
 Description Bi-Metallic Pin Terminals  
 Solid Copper Pin  
 Straight Pin

**Features**

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro Tin Plated
- AL9CU Rated for Copper or Aluminum Conductors
- Oxide Inhibitor Coated Barrel
- EDPM Rubber Insulating Cover



**General**

Material: Aluminum Alloy  
 EDPM Rubber Insulating Cover  
 Wire Range: Conductor Size Pin Size  
 #6 #4  
 Thru 750 MCM Thru 500 MCM

**Dimension Information**

Length: See Table

**Specifications**

Temperature Rating: N/A  
 Voltage Rating: 600  
 Flammability Rating: N/A  
 Amp Rating: To Conductor

**Packaging**

Box Qty See Table

**Certifications**

UL Yes  
 cUL Yes  
 RoHS Yes

Cat. No.	Wire Size	Pin Size	O.D.	I.D.	Pin Dia.	Total Length	Pin Length	Body Length	Color Code	Inner Box	Outer Box
90970	6	4	0.598	0.22	0.24	1.85	0.681	1.17	Tan	25	250
90971	4	4	0.598	0.236	0.24	1.85	0.681	1.17	Tan	25	250
90972	2	4	0.598	0.299	0.24	1.84	0.68	1.16	Tan	25	250
90973	1	3	0.598	0.318	0.25	1.99	0.83	1.16	Tan	10	100
90974	1/0	2	0.598	0.37	0.29	1.99	0.83	1.16	Tan	10	100
90975	2/0	1	0.85	0.429	0.33	2.2	0.83	1.37	White	10	100
90976	3/0	1/0	0.85	0.476	0.37	2.59	1.22	1.37	White	10	100
90977	4/0	2/0	0.85	0.476	0.37	2.59	1.22	1.37	White	10	100
90978	250 MCM	3/0	1.09	0.594	0.46	2.62	1.22	1.4	Brown	10	100
90979	300 MCM	4/0	1.09	0.653	0.53	2.73	1.33	1.4	Brown	10	100
90980	350 MCM	250	1.09	0.716	0.57	2.73	1.33	1.4	Brown	10	100
90981	400 MCM	300	1.31	0.763	0.62	3.07	1.59	1.48	Pink	10	100
90982	500 MCM	350	1.31	0.826	0.68	3.07	1.59	1.48	Pink	10	100
90983	600 MCM	400	1.46	0.921	0.72	3.67	1.64	2.03	Yellow	3	30
90984	750 MCM	500	1.46	1.03	0.81	3.78	1.75	2.03	Yellow	3	30