



Catalog Number See Table
UPC Number
Description Copper Short Barrel Compression Splice




Features

- Manufactured from High Strength High Conductivity Seamless Copper Tubing
- Electro-Tin Plated
- Color coded & Marked with die size and crimp marks

General

Wire Size #8 Str thru 1000 MCM
Material High Conductivity Seamless Copper Tubing
Material Treatment Electro-Tin Plating



Dimension Information

See Table

Specifications

Temperature Rating 90° C
Voltage Rating 35 KV
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL486A
cUL Yes
RoHS Yes



Copper Short Barrel 1 Hole Compression Connector

Cat No.	Wire Range	Color Code	Box Qty	Inside Diameter	Outside Diameter	Length	
94410	8 Str.	Red	80	.172(4.4)	.272(6.9)	1.06(26.9)	
94412	6 Str.	Blue	60	.203(5.2)	.297(7.5)	1.73(43.9)	
94414	4 Str.	Gray	45	.250(6.4)	.344(8.7)	1.73(43.9)	
94416	2 Str.	Brown	25	.315(8.0)	.422(10.7)	1.85(47.0)	
94418	1 Str.	Green	20	.360(9.1)	.469(11.9)	1.85(47.0)	
94420	1/0 Str.	Pink	15	.390(9.9)	.520(13.2)	1.85(47.0)	
94422	2/0 Str.	Black	10	.441(11.2)	.563(14.3)	2.01(51.1)	
94424	3/0 Str.	Orange	20	.492(12.5)	.622(15.8)	2.13(54.1)	
94426	4/0 Str.	Purple	20	.547(13.9)	.688(17.5)	2.13(54.1)	
94428	250 MCM	Yellow	20	.594(15.1)	.750(19.1)	2.24(56.9)	
94430	300 MCM	White	18	.658(16.7)	.813(20.7)	2.24(56.9)	
94432	350 MCM	Red	15	.700(17.8)	.875(22.2)	2.36(59.9)	
94434	400 MCM	Blue	10	.764(19.4)	.949(24.1)	2.52(64.0)	
94436	500 MCM	Brown	6	.835(21.2)	1.063(27.0)	2.87(72.9)	
94438	600 MCM	Green	4	.925(23.5)	1.188(30.2)	2.87(72.9)	
94440	750 MCM	Black	3	1.03(26.2)	1.31(33.3)	3.39(86.1)	
94442	1000 MCM	—	1	1.19(30.2)	1.53(38.8)	3.70 (94.0)	

www.morrisproducts.com

Morris Products

53 Carey Road

Queensbury, NY 12804