

The global leader in  
door opening solutions

## Rockwood 2948 - Automatic Flush Bolt with Bottom for Fire Rated Wood Doors Fire Bolt



### Specifications:

#### MATERIAL:

Brass, Stainless Steel

#### FASTENERS:

8 ea. #8 x  $\frac{3}{4}$ " Flat Head Combo Screws, 2 ea. Plastic Anchors; 3 ea. #10 x 1" Flat Head Wood Screws

#### FEATURES:

- Non-handed
- Low (5 lbs. maximum) closing force
- Fully automatic; opening active door retracts top bolt
- Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to  $\frac{1}{2}$ "
- For fire rated UL listed 20-minute wood core and composite doors up to 4'w x 9'h
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment
- UL Listed



### Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US32D/630

#### SIZE:

Top Bolt: 1" x 8  $\frac{1}{2}$ "

Bottom Bolt:  $\varnothing$   $\frac{13}{16}$ "

#### WEIGHT:

1.6 lbs.

300 Main Street

Rockwood, Pennsylvania 15557

P: 800.458.2424 • F: 800.922.9212

www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.